

# Power Supply

## CUSTOMISED OPEN FRAME POWER SUPPLY



### [ OUTLINES ]

Open Frame Power Supply is specially developed for the use in LCD-TVs.

### [ FEATURES ]

- low level noise (TV picture noise)
- 6 output voltages/all regulated
- safety class II acc. to EN60065/EN60950
- low level standby consumption (less than 0,2W possible)

### [ SPECIFICATIONS ]

ENVIRONMENTAL CHARACTERISTICS				
Operation Temperature	0°C -+ 40°C			
Storage Temperature	-15°C - +65°C			
Cooling Condition	Convection cooling			
Operation Environment	Indoor			
INPUT CHARACTERISTICS				
Input Voltage (Vin)	Rated: 230-240Vac/+-10% Single Phase			
Input Frequency	Rated: 50 Hz Range: 47-53 Hz			
Input Power	380W max. @max. ouput power within rated Vin			
Standby Power	<2W @10V/75mA main converter switched off			
Efficiency	85% @ min.			
Output Voltage	24V	5V	15V	10V
Output Current	6,7A	6,7A	0,4A	0,4A

**POWER**  
 Panasonic Electronic Devices Europe GmbH  
**SUPPLY**

Design and Specifications are subject to change without notice. Ask the factory for technical specifications before purchase and/or use. If there is any doubt regarding the safety of this product, kindly inform us immediately for technical consultation.

# Panasonic ideas for life



## CONTACT

Dipl.-Ing.  
**Robert Sippel**  
Product Manager  
Power Supply/Control & Drives  
Zeppelinstrasse 19  
21337 Lüneburg, Germany

Tel. (49)-4131-899-312  
Fax (49)-4131-899-187  
Robert.Sippel@eu.panasonic.com